

Polycom[®] KIRK[®] Base Station

System Capacity

- Max. number of speech channels: 4
- Circular coverage area: Typical range indoor: 20-50 m, outdoor: 600 m

Radio Interface

- Average transmit power: typical 10mW/ch. (EU DECT), 5mW/ch. (US DECT)
- Peak transmit power: typical 250mW (EU DECT), 125mW (US DECT)
- Receiver sensitivity: typical -90 dBm.
- Frequency Bands available:
 - EU DECT (1880-1900 MHz)
 - US DECT (1920-1930 MHz)
 - Other DECT frequency bands are also available on request

Radio Approvals

- EN 301 406 V1.5.1 (EU DECT)
- FCC RULES PART 15/Subpart D, RSS-213 (US DECT)

Electro Magnetic Compatibility (EMC) Approvals (Regulatory EU DECT Standards)

- EN 301 489-1
- EN 301 489-6

Safety (Regulatory Standards)

- UL60950-1 CAN/CSA-C22.2 No. 60950-1-03
- EN 60950-1: 2001 + A11 2004

Environmental Conditions of the Installation Area

- Relative humidity: Between 20% and 80% (non-condensing)
- Temperature range: Between 0°C and +55°C/32°F and 131°F.
- The equipment is in compliance with the requirements of EU directive 2002/95/EC (ROHS) and 2002/96/EC (WEEE)

Electrical Requirements

- Power consumption: 0.98W (Max. 1.23W)
- The power supply is 48 VDC, 21mA (Powered from the server)

Physical Characteristics

- Size (W: 10.0 x H: 3.0 x D: 10.0 cm)
- Weight: 113 g
- Grey-white (NCS 0502-Y)
- Wall-mountable, indoor

Polycom KIRK Base Stations

Polycom Worldwide Headquarters
4750 Willow Road, Pleasanton, CA 94588
1.800.POLYCOM or +1.925.924.6000 | www.polycom.com



© 2009, Polycom, Inc. All rights reserved. POLYCOM®, the Polycom "Triangles" logo and the names and marks associated with Polycom's products are trademarks and/or service marks of Polycom, Inc. and are registered and/or common law marks in the United States and various other countries. All other trademarks are property of their respective owners. No portion hereof may be reproduced or transmitted in any form or by any means, for any purpose other than the recipient's personal use, without the express written permission of Polycom.